



DEARING OF AMERICA CORP.



SKF SYH 1.15/16 WF bearing units

Bearing No. SYH 1.15/16 WF

SYH 1.15/16 WF Bearing 2D drawings and 3D CAD models

Bore Diameter	49,213 mm
d	49,213 mm
s1	38,1 mm
A	54 mm
A1	34 mm
B1	62,7 mm
H	113,5 mm
H1	55,6 mm
H2	21,4 mm
J	157 mm
L	203 mm
N	26 mm
N1	18 mm
Thread (G)	16
Weight	2,95 Kg
Basic dynamic load rating (C)	35,1 kN
Basic static load rating (C0)	23,2 kN
Fatigue load limit (Pu)	0,98
Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	2.82
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Eccentric Collar



DEARING OF AMERICA CORP.

Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	5/8 Inch
Relubricatable	Yes
Insert Part Number	YEL 210-115-2F
Seals	M Seal
Housing Configuration	1 Piece Solid
Inch - Metric	Inch
Other Features	Single Row Standard Duty Wide Inner Race Low Base Has Flinger
Long Description	2 Bolt Pillow Block; 1-15/16" Bore; 2-3/16" Base to Center Height; Eccentric Collar Mount; Ball Bearing; 5-7/8" Minimum Bolt Spacing; 6-1/2" Bolt Spacing Maximum; Relubricatable; C
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	SYH 1.15/16 WF
Weight / LBS	6.7
Length Thru Bore	2.469 Inch 62.7 Millimeter
Nominal Bolt Center to Center	6.3 Inch 160 Millimeter
Bolt Spacing Maximum	6.5 Inch 165.1 Millimeter
Base to Center Height	2.188 Inch 55.575 Millimeter



DEARING OF AMERICA CORP.

Actual Bolt Center to Center	0 Inch 0Millimeter
Bore	1.938 Inch 49.225 Millimeter
Bolt Spacing Minimum	5.875 Inch 149.225Millimeter